

SC200SR



SC200SR



Engine Type	Single Cylinder, 4-stroke, 4-valve, SOHC
Displacement (cc)	169
Bore x Stroke (mm)	61 x 57.8
Compression Ratio	11.2:1
Maximum Power	11.9 kW @ 8,000 rpm
Maximum Torque	15.1 N.m @ 7,000 rpm
Cooling System	Liquid-cooled, Lateral-mounted Engine
Clutch / Transmission	Automatic / V-Belt
Lubrication System	Pressure Splash Lubricant
Starting System	Electric
Fuel System	EFI
Front Suspension	Telescopic Forks
Rear Suspension	Monoshock, Preload Adjustable
Front Brake	Disc, 2-piston Calipers
Front Brake Diameter (mm)	260
Rear Brake	Disc, 1-piston Caliper
Rear Brake Diameter (mm)	233
Front Tyre	120/70-R13, CST
Rear Tyre	130/70-R13, CST
Dashboard Type	LCD
Tyre Pressure Monitoring System (TPMS)	Available
Length x Width x Height (mm)	1,990 X 765 X 1,160
Wheelbase (mm)	1,395
Seat Height (mm)	780
Ground Clearance (mm)	125
Fuel Tank Capacity (L)	7.8
Curb Weight (kg)	142
Battery	12v8.6Ah
Colour	Kingfisher Green, Bulk Black, Sprint Purple

BULK BLACK



KINGFISHER GREEN



SPRINT PURPLE



**Specifications and features are subject to change without prior notice.*

Distributed by
mforce
MOVING FORWARD

MFORCE BIKE HOLDINGS SDN. BHD.(751410-H)
1485, Jalan Seruling, Kawasan Perindustrian Valdor, 14200 Sungai Jawi, Pulau Pinang, Malaysia.
Tel: 604-545 2222 | Fax: 604-545 2288 | Email: help@mforce.my

MFORCE OIL
POWERED BY PETRONAS